

Auto darkening welding helmet SPARTUS Easy

Product code: 080-10-100

Product description

SPARTUS Easy Auto Darkening welding helmet. Designed for eye and face protection welder against harmful radiation and welding spatter. Intended for use when welding methods: MMA, MIG/MAG, TIG and plasma cutting. It has extra grinding function.

Lightweight construction and ergonomic design provides properly comfortable working. This model has an automatic welding filter with active field of view equal 98x43mm. It has 2 highly sensitive sensors. Light to dark switching time is only 1/25000 of a second. Shading standby DIN 4 allows easy material preparation before welding and its further processing after welding.

Infinitely adjustable sensitivity, delay control and variable welding shades. Interchangeable protective welding filter shields. This system meets the requirements of security according to Annex II of EU Directive 86/686/EEC. This product is labeled with CE mark.

Top filter characteristics:

Easy to use

Variable welding shades DIN 9 - 13

Sensitivity control

Delay control

TEST button

Active field of view 98x43mm

Technical parameters

Brand	SPARTUS Easy
Application	MMA welding, TIG welding, MIG/MAG welding
Cartridge size [mm]	110 x 90 x 9
Active field of view [mm]	98 x 43
UV/IR protection degree	do DIN16
Light to dark switching time	1/25000 s
Delay control of light to dark switching time	0.1 - 1.0s
Powered	Solar cells
Grinding	YES
Weight	480 g

PRODUCT CATEGORIES: ACCESSORIES

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.