

## EasyTIG torch 225F / 8m / mini 1B / D / control plug SK35


**Product code:**

SPE225FA-8-MSRE1B-D-1BEZ

### Technical parameters

<b>Rating</b>	200A DC 170A AC
<b>Electrode diameter [mm]</b>	0.5, 1.0, 1.6, 2.0, 2.4, 3.2
<b>Gas flow rate [L/min]</b>	7 - 20
<b>Liquid cooling flow [L/min]</b>	1.0 - 1.5
<b>Duty cycle [%]</b>	80
<b>Series</b>	Easy
<b>Cooling</b>	liquid
<b>Torch body</b>	225F [replacement heads]
<b>Torch body</b>	standard
<b>Head type</b>	9-70 [small parts]
<b>Lenght [m]</b>	8
<b>Handle</b>	standard
<b>Microswitch</b>	single
<b>Package</b>	rubber cable cover
<b>Control plug</b>	SK35

 PRODUCT CATEGORIES: [TIG](#), [TIG TORCHES](#), [MIG GUNS](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.