

EasyTIG torch 9 / 8m / mini 1B / X / SK35 control plug



Product code:

SPE9-8-mSRE1B-X-1BEZ

Product description

SPARTUS® Easy TIG torches are a perfect combination of quality and simplicity of workmanship. Tig torches are designed for easy operation and comfortable work. The flexible and lightweight cable package and ergonomic handle guarantee comfortable work.

3 main advantages of SPARTUS® Easy TIG torches:

- high quality and simplicity of manufacture
- manufacturing any length in the range of 4 – 25m
- compliance with EU standards

MICROSWITCH

With an additional cost, SPARTUS® welding torches can be equipped with other microswitches:

Microswitch



2B



4B



5K/10K (with potentiometer)

CONTROL PLUG

With an extra cost, SPARTUS® welding torches can be also equipped with control plug to the most leading makes of welding machines.

See control plugs - [HERE](#)

Technical parameters

Rating	125A DC 100A AC
Electrode diameter [mm]	0.5, 1.0, 1.6, 2.0, 2.4
Gas flow rate [L/min]	7 - 15
Duty cycle [%]	35
Series	Easy
Cooling	gas
Torch body	9 [small parts]
Torch body	standard
Length [m]	8
Handle	mini

Microswitch	single
Package	textile-rubber + 1m leather cable cover after grip
Connections	SK35

PRODUCT CATEGORIES: [TIG TORCHES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.