

## MasterTIG torch 125F / head TIG 9 / 8m / 1F / X / SK35 control plug



**Product code:** SPM125FA-8-SW1F-X-1BEZ

## Technical parameters

Rating	125A DC 100A AC
Electrode diameter [mm]	0.5, 1.0, 1.6, 2.0, 2.4
Gas flow rate [L/min]	7 - 15
Duty cycle [%]	60
Series	Master
Cooling	gas
Torch body	125F [replcement heads]
Torch body	flex
Head type	9-70 [small parts]
Lenght [m]	8
Handle	round
Microswitch	convex
Package	textile-rubber + 1m leather cable cover after grip
Connections	SK35

## PRODUCT CATEGORIES: TIG TORCHES

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

 $\label{thm:constitute} \textit{The products do not constitute an offer within the meaning of the Civil Code}.$