

MasterTIG torch 150R / head TIG 9 / head TIG 9 / 4m / mini 1B / X / control plug SK35

Product code:

SPM150RA-4-MSRM1B-X-1BEZ



Product description

The SPARTUS® 150R TIG torch is a solution that allows the use of 2 types of rotary heads:

torch head SP 9 [small parts] torch head SP 17 [large parts]



Thanks to the replaceable torch head, the conversion of the torch takes about the same as replacing consumable parts.

You can choose the following TIG torch:

150FA with torch head SP 9 [125A DC] 150FB with torch head SP 17 [150A DC]

MICROSWITCH

With an additional cost, SPARTUS® welding torches can be equipped with other microswitches:

2B	-
4B	10,13€
5K/10K (witch potentiometer)	28,58€

CONTROL PLUG

With an extra cost, SPARTUS® welding torches can be also equipped with control plug to the most leading makes of welding machines. Connection table below. See control plugs - HERE



2SPA 1ESB 4SPA 1EWM 5SPA 1MAG 8SPA 2MAG 9SPA 1ASP 1FAL 2ASP 2FAL 1LIN	4,86 €
1EUR 1KMP 1FRO 2KMP	7,77 €
1CEA 2ESB	17,49 €
2FRO	42,75 €

Technical parameters

Rating	125A DC 100A AC
Electrode diameter [mm]	0.5, 1.0, 1.6, 2.0, 2.4
Gas flow rate [L/min]	7 - 15
Duty cycle [%]	60
Series	Master
Cooling	gas
Torch body	150R [rotary head]
Torch head type	9-90R [small parts]
Torch body	standard
Lenght [m]	4
Handle	mini
Microswitch	single
Package	textile-rubber + 1m leather cable cover after grip
Connections	SK35

PRODUCT CATEGORIES: TIG TORCHES

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, LTEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.