

MasterTIG torch 150R / head TIG 9 / 8m / mini 1B / X / control plug SK35



**Product code:**

SPM150RA-8-MSRM1B-X-1BEZ

**Technical parameters**

<b>Rating</b>	125A DC 100A AC
<b>Electrode diameter [mm]</b>	0.5, 1.0, 1.6, 2.0, 2.4
<b>Gas flow rate [L/min]</b>	7 - 15
<b>Duty cycle [%]</b>	60
<b>Series</b>	Master
<b>Cooling</b>	gas
<b>Torch body</b>	150R [rotary head]
<b>Torch body</b>	standard
<b>Torch head type</b>	9-90R [small parts]
<b>Lenght [m]</b>	8
<b>Handle</b>	mini
<b>Microswitch</b>	single
<b>Package</b>	textile-rubber + 1m leather cable cover after grip
<b>Connections</b>	SK35

PRODUCT CATEGORIES: [TIG TORCHES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.