

## MasterTIG torch 17 / 8m / mini 1B / X / SK35 control plug



**Product code:**

SPM17-8-mSRM1B-X-1BEZ

### Product description




For many years, SPARTUS® Master welding torches have been widely valued by professionals. Master TIG torches are an adequate combination of high quality workmanship, excellent parameters and ergonomics. A high-class, durable cable package along with a power cable can conduct high amperages.

4 main advantages of SPARTUS® Master TIG torches:

- high quality and simplicity of manufacture
- manufacturing any length in the range of 4 - 25m
- durable and flexible cable package
- compliance with EU standards

### MICROSWITCH

With an additional cost, SPARTUS® welding torches can be equipped with other microswitches:

	Microswitch
	2B
	4B
	5K/10K (with potentiometer)

### CONTROL PLUG

With an extra cost, SPARTUS® welding torches can be also equipped with control plug to the most leading makes of welding machines.

See control plugs - [HERE](#)

### Technical parameters

<b>Rating</b>	150A DC 115A AC
<b>Electrode diameter [mm]</b>	0.5, 1.0, 1.6, 2.0, 2.4, 3.2
<b>Gas flow rate [L/min]</b>	7 - 15
<b>Duty cycle [%]</b>	60
<b>Series</b>	Master
<b>Cooling</b>	gas
<b>Torch body</b>	17 [large parts]
<b>Torch body</b>	standard
<b>Lenght [m]</b>	8
<b>Handle</b>	mini

<b>Microswitch</b>	single
<b>Package</b>	textile-rubber + 1m leather cable cover after grip
<b>Connections</b>	SK35

PRODUCT CATEGORIES: [TIG TORCHES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.