

## MasterTIG torch 18 / 4m / 1B / Z / control plug SK35



**Product code:** SPM18-4-SRM1B-Z-1BEZ

**Referention number:** uchwyt TIG 18; uchwyt WP 18; uchwyt sr 18; uchwyt srt 18; uchwyt sp 18

### Technical parameters

<b>Rating</b>	350A DC 250A AC
<b>Electrode diameter [mm]</b>	0.5, 1.0, 1.6, 2.0, 2.4, 3.2, 4.0
<b>Gas flow rate [L/min]</b>	7 - 20
<b>Liquid cooling fflow [L/min]</b>	1.0 - 1.5
<b>Duty cycle [%]</b>	100
<b>Series</b>	Master
<b>Cooling</b>	liquid
<b>Torch body</b>	18 [large parts]
<b>Torch body</b>	standard
<b>Lenght [m]</b>	4
<b>Handle</b>	standard
<b>Microswitch</b>	single
<b>Package</b>	leather cable cover
<b>Control plug</b>	SK35

PRODUCT CATEGORIES: [TIG TORCHES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.