

## MasterTIG torch 18SC / 4m / 1B / Z / control plug SK35

**Product code:** 



SPM18SC-4-SRM1B-Z-1BEZ

## **Technical parameters**

Rating	400A DC 280A AC
Electrode diameter [mm]	0.5, 1.0, 1.6, 2.0, 2.4, 3.2, 4.0, 4.8
Gas flow rate [L/min]	7 - 20
Liquid cooling floow [L/min]	1.0 - 1.5
Duty cycle [%]	100
Series	Master
Cooling	liquid
Torch body	18SC [large parts]
Torch body	standard
Lenght [m]	4
Handle	standard
Microswitch	single
Package	leather cable cover
Control plug	SK35

## PRODUCT CATEGORIES: TIG TORCHES

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.