

MasterTIG torch 18SC / 8m / 1B / Z / control plug SK35



Product code: SPM18SC-8-SRM1B-Z-1BEZ

Technical parameters

| | |
|-----------------------------|--|
| Rating | 400A DC 280A AC |
| Electrode diameter [mm] | 0.5, 1.0, 1.6, 2.0, 2.4, 3.2, 4.0, 4.8 |
| Gas flow rate [L/min] | 7 - 20 |
| Duty cycle [%] | 100 |
| Liquid cooling flow [L/min] | 1.0 - 1.5 |
| Series | Master |
| Cooling | liquid |
| Torch body | 18SC [large parts] |
| Torch body | standard |
| Lenght [m] | 8 |
| Handle | standard |
| Microswitch | single |
| Package | leather cable cover |
| Control plug | SK35 |

PRODUCT CATEGORIES: [TIG TORCHES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.