

# MasterTIG torch 20HD / 4m / mini 1B / Z / control plug SK35



Product code: SPM20HD-4-MSRM1B-Z-1BEZ

## Technical parameters

Rating	300A DC 220A AC
Electrode diameter [mm]	0.5, 1.0, 1.6, 2.0, 2.4, 3.2
Gas flow rate [L/min]	7 - 20
Liquid cooling flow [L/min]	1.0 - 1.5
Duty cycle [%]	100
Series	Master
Cooling	liquid
Torch body	20hd [small parts]
Torch body	standard
Lenght [m]	4
Handle	mini
Microswitch	single
Package	leather cable cover
Control plug	SK35

PRODUCT CATEGORIES: [TIG TORCHES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.