

MasterTIG torch 225F / 8m / mini 1B / X / control plug SK35


Product code:

SPM225FA-8-MSRM1B-X-1BEZ

Technical parameters

Rating	200A DC 170A AC
Electrode diameter [mm]	0.5, 1.0, 1.6, 2.0, 2.4, 3.2
Gas flow rate [L/min]	7 - 15
Liquid cooling flow [L/min]	1.0 - 1.5
Duty cycle [%]	100
Series	Master
Cooling	liquid
Torch body	225F [replacement heads]
Torch body	standard
Head type	9-70 [small parts]
Lenght [m]	8
Handle	standard
Microswitch	single
Package	textile-rubber + 1m leather cable cover after grip
Control plug	SK35

 PRODUCT CATEGORIES: [TIG](#), [TIG TORCHES](#), [MIG GUNS](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.