

MasterTIG torch 225F / 8m / mini 1B / Z / control plug SK35

	Product code:	SPM225FA-8-MSRM1B-Z-1BEZ
Technical parameters		
Rating		200A DC 170A AC
Electrode diameter [mm]		0.5, 1.0, 1.6, 2.0, 2.4, 3.2
Gas flow rate [L/min]		7 - 20
Liquid cooling floow [L/min]		1.0 - 1.5
Duty cycle [%]		100
Series		Master
Cooling		liquid
Torch body		225F [replcement heads]
Torch body		standard
Head type		9-70 [small parts]
Lenght [m]		8
Handle		standard
Microswitch		single
Package		leather cable cover
Control plug		SK35

PRODUCT CATEGORIES: TIG, TIG TORCHES, MIG GUNS

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.