

MasterTIG torch 9 / 8m / mini 1B / X / SK35 control plug



Product code:

SPM9-8-mSRM1B-X-1BEZ

Product description




For many years, SPARTUS® Master welding torches have been widely valued by professionals. Master TIG torches are an adequate combination of high quality workmanship, excellent parameters and ergonomics. A high-class, durable cable package along with a power cable can conduct high amperages.

4 main advantages of SPARTUS® Master TIG torches:

- high quality and simplicity of manufacture
- manufacturing any length in the range of 4 – 25m
- durable and flexible cable package
- compliance with EU standards

MICROSWITCH

With an additional cost, SPARTUS® welding torches can be equipped with other microswitches:

	Microswitch
	2B
	4B
	5K/10K (with potentiometer)

CONTROL PLUG

With an extra cost, SPARTUS® welding torches can be also equipped with control plug to the most leading makes of welding machines.

See control plugs - [HERE](#)

Technical parameters

Rating	125A DC 100A AC
Electrode diameter [mm]	0.5, 1.0, 1.6, 2.0, 2.4
Gas flow rate [L/min]	7 - 15
Duty cycle [%]	60
Series	Master
Cooling	gas
Torch body	9 [small parts]
Torch body	standard
Length [m]	8
Handle	mini

Microswitch	single
Package	textile-rubber + 1m leather cable cover after grip
Connections	SK35

PRODUCT CATEGORIES: [TIG TORCHES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.