

## ProTIG torch 12 / 4m / 1B / X / control plug SK35

**Product code:** SPP12-4-04280-X-1BEZ

### Technical parameters

<b>Rating</b>	500A DC 350A AC
<b>Electrode diameter [mm]</b>	1.6, 2.0, 2.4, 3.2, 4.0, 4.8, 6.4
<b>Gas flow rate [L/min]</b>	7 - 20
<b>Duty cycle [%]</b>	100 [super flex]
<b>Liquid cooling flow [L/min]</b>	1.0 - 1.5
<b>Series</b>	Pro
<b>Cooling</b>	liquid
<b>Torch body</b>	12 [machine]
<b>Torch body</b>	standard
<b>Lenght [m]</b>	4
<b>Handle</b>	standard
<b>Microswitch</b>	single
<b>Package</b>	textile-rubber + 1m leather cable cover after grip
<b>Control plug</b>	SK35

PRODUCT CATEGORIES: [TIG TORCHES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.