

ProTIG torch 12 / 4m / 1B / X / control plug SK35

Product code:

SPP12-4-04280-X-1BEZ

Technical parameters

Rating	500A DC 350A AC
Electrode diameter [mm]	1.6, 2.0, 2.4, 3.2, 4.0, 4.8, 6.4
Gas flow rate [L/min]	7 - 20
Duty cycle [%]	100 [super flex]
Liquid cooling flow [L/min]	1.0 - 1.5
Series	Pro
Cooling	liquid
Torch body	12 [machine]
Torch body	standard
Lenght [m]	4
Handle	standard
Microswitch	single
Package	textile-rubber + 1m leather cable cover after grip
Control plug	SK35

PRODUCT CATEGORIES: [TIG TORCHES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.