

ProTIG torch 125F / head TIG 9 / 4m / 1F / Z / SK35 control plug


Product code:

SPP125FA-4-SW1F-Z-1BEZ

Technical parameters

| | |
|--------------------------------|--------------------------|
| Rating | 125A DC 100A AC |
| Electrode diameter [mm] | 0.5, 1.0, 1.6, 2.0, 2.4 |
| Gas flow rate [L/min] | 7 - 15 |
| Duty cycle [%] | 80 |
| Series | Pro |
| Cooling | gas |
| Torch body | 125F [replacement heads] |
| Torch body | flex |
| Head type | 9-70 [small parts] |
| Lenght [m] | 4 |
| Handle | round |
| Microswitch | convex |
| Package | leather cable cover |
| Connections | SK35 |

 PRODUCT CATEGORIES: [TIG TORCHES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.