

ProTIG torch 125F / head TIG 9 / 4m / 1F / Z / SK35 control plug



Product code: SPP125FA-4-SW1F-Z-1BEZ

Technical parameters

Rating	125A DC 100A AC
Electrode diameter [mm]	0.5, 1.0, 1.6, 2.0, 2.4
Gas flow rate [L/min]	7 - 15
Duty cycle [%]	80
Series	Pro
Cooling	gas
Torch body	125F [replacement heads]
Torch body	flex
Head type	9-70 [small parts]
Lenght [m]	4
Handle	round
Microswitch	convex
Package	leather cable cover
Connections	SK35

PRODUCT CATEGORIES: [TIG TORCHES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.