

ProTIG torch 18 / 4m / 1B / X / control plug SK35



Product code: SPP18-4-SRP1B-X-1BEZ

Referention number: uchwył TIG 18; uchwył WP 18; uchwył sr 18; uchwył srt 18; uchwył sp 18

Technical parameters

| | |
|------------------------------------|--|
| Rating | 350A DC 250A AC |
| Electrode diameter [mm] | 0.5, 1.0, 1.6, 2.0, 2.4, 3.2, 4.0 |
| Gas flow rate [L/min] | 7 - 20 |
| Liquid cooling flow [L/min] | 1.0 - 1.5 |
| Duty cycle [%] | 100 [super flex] |
| Series | Pro |
| Cooling | liquid |
| Torch body | 18 [large parts] |
| Torch body | standard |
| Lenght [m] | 4 |
| Handle | standard |
| Microswitch | single |
| Package | textile-rubber + 1m leather cable cover after grip |
| Control plug | SK35 |

PRODUCT CATEGORIES: [TIG TORCHES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.