

ProTIG torch 18 / 8m / 1B / X / control plug SK35



Product code: SPP18-8-SRP1B-X-1BEZ

Referention number: uchwyt TIG 18; uchwyt WP 18; uchwyt sr 18; uchwyt srt 18; uchwyt sp 18

Technical parameters

Rating	
Electrode diameter [mm]	0.5, 1.0, 1.6, 2.0, 2.4, 3.2, 4.0
Gas flow rate [L/min]	7 - 20
Liquid cooling flow [L/min]	1.0 - 1.5
Duty cycle [%]	100 [super flex]
Series	Pro
Cooling	liquid
Torch body	18 [large parts]
Torch body	standard
Lenght [m]	8
Handle	standard
Microswitch	single
Package	textile-rubber + 1m leather cable cover after grip
Control plug	SK35

PRODUCT CATEGORIES: [TIG TORCHES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.