

ProTIG torch 18SC / 8m / 1B / Z / control plug SK35



Product code:

SPP18SC-8-SRP1B-Z-1BEZ

Technical parameters

Rating	400A DC 280A AC
Electrode diameter [mm]	0.5, 1.0, 1.6, 2.0, 2.4, 3.2, 4.0, 4.8
Gas flow rate [L/min]	7 - 20
Liquid cooling floow [L/min]	1.0 - 1.5
Duty cycle [%]	100 [super flex]
Series	Pro
Cooling	liquid
Torch body	18SC [large parts]
Torch body	standard
Lenght [m]	8
Handle	standard
Microswitch	single
Package	leather cable cover

PRODUCT CATEGORIES: TIG TORCHES

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, LTEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

 $\label{thm:constitute} \textit{The products do not constitute an offer within the meaning of the Civil Code}.$