

ProTIG torch 225F / 8m / mini 1B / X / control plug SK35



Product code:

SPP225FA-8-MSRP1B-X-1BEZ

Technical parameters

| | |
|------------------------------------|--|
| Rating | 200A DC 170A AC |
| Electrode diameter [mm] | 0.5, 1.0, 1.6, 2.0, 2.4, 3.2 |
| Gas flow rate [L/min] | 7 - 20 |
| Liquid cooling flow [L/min] | 1.0 - 1.5 |
| Duty cycle [%] | 100 [super flex] |
| Series | Pro |
| Cooling | liquid |
| Torch body | 225F [replacement heads] |
| Torch body | standard |
| Head type | 9-70 [small parts] |
| Length [m] | 8 |
| Handle | standard |
| Microswitch | single |
| Package | textile-rubber + 1m leather cable cover after grip |
| Control plug | SK35 |

PRODUCT CATEGORIES: [TIG](#), [TIG TORCHES](#), [MIG GUNS](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.