

## ProTIG torch 24W / 8m / mini 1B / X / control plug SK35



**Product code:**

SPP24W-8-mSRP1B-X-1BEZ

### Technical parameters

<b>Rating</b>	180A DC 100A AC
<b>Electrode diameter [mm]</b>	0.5, 1.0, 1.6, 2.0, 2.4
<b>Gas flow rate [L/min]</b>	7 - 20
<b>Liquid cooling flow [L/min]</b>	1.0 - 1.5
<b>Duty cycle [%]</b>	100
<b>Series</b>	Pro
<b>Cooling</b>	liquid
<b>Torch body</b>	24W [small parts]
<b>Torch body</b>	standard
<b>Lenght [m]</b>	8
<b>Handle</b>	mini
<b>Microswitch</b>	single
<b>Package</b>	textile-rubber + 1m leather cable cover after grip
<b>Control plug</b>	SK35

PRODUCT CATEGORIES: [TIG TORCHES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.