

PT100M Machine torch 6m (central connector) (coaxial cable)



**Product code:**

09735CX

**Technical parameters**

<b>type of torch</b>	machine
<b>Type PT™</b>	PT100
<b>Cutting current [A]</b>	30 - 100
<b>Gas</b>	Air / N2
<b>Duty cycle [%]</b>	60
<b>Operating pressure [bar]</b>	4.6 - 5
<b>Air flow [l/min]</b>	200
<b>A way of arc ignition</b>	without HF
<b>Pilot arc [A]</b>	18 - 22
<b>Lenght [m]</b>	12
<b>Connection</b>	1/4"

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.