

## PT80H Hand torch 12m (1/4")



09825



## Technical parameters

| Standard                 | PT™        |
|--------------------------|------------|
| type of torch            | hand       |
| Type PT™                 | PT80       |
| Cutting current [A]      | 30 - 80    |
| Gas                      | Air / N2   |
| Duty cycle [%]           | 60         |
| Operating pressure [bar] | 4.4 - 5    |
| Air flow [I/min]         | 160        |
| A way of arc ignition    | without HF |
| Pilot arc [A]            | 18 - 22    |
| Lenght [m]               | 12         |
| Connection               | 1/4"       |

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

 $\label{thm:constitute} \textit{The products do not constitute an offer within the meaning of the Civil Code}.$