

# Screw compressor SP15B-1400-15



Product code: SP15B-1400-15

## Product description

- Advantages of the device:
- reliable screw airends by global manufacturers (GHH RAND) designed for continuous operation,
  - asymmetric design rotor's profiles to generate maximum power and performance at minimum energy cost,
  - low-noise operation (67 dB),
  - belt drive enabling easy modification of performance and maximum pressure by changing the pulley ratios,
  - simplified access to maintain the airend,
  - microprocessor controller with idle run function.

## Technical parameters

Input	~3× 400V ± 10% 50 / 60 Hz
Max. Pressure [bar]	15
Capacity [l/min]	1400
Power [kW]	15
Noise level [dB(A)]	67
Connection [cal]	3/4
Weight [kg]	335
Dimensions [mm]	1125 x 810 x 1180

PRODUCT CATEGORIES: [PNEUMATICS](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.