

SP1650M machine plasma torch 7,5m (connection POWERMAX® 1650)



Product code:

03831CX-HY

Technical parameters

Standard	SPARTUS®
type of torch	machine
Type SPARTUS®	SP1650
Cutting current [A]	100
Gas	Air / N2
Duty cycle [%]	85
Operating pressure [bar]	5.1 bar (~70psi)
Air flow [l/min]	260
A way of arc ignition	without HF
Lenght [m]	7.5
Connection	PowerMax1650®
Thickness of cutting plate [mm]	MAX: 19 ; Zalecane: 12

PRODUCT CATEGORIES: [PLASMA](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.