

SP70H Handheld plasma torch 6m (connection 1/8")



Product code:

03070/LT

Technical parameters

| | |
|--------------------------|--------------------|
| Standard | SPARTUS® |
| type of torch | hand |
| Type SPARTUS® | SP70 |
| Cutting current [A] | 70 |
| Gas | Air / N2 |
| Duty cycle [%] | 60 |
| Operating pressure [bar] | 4.5 - 5 (70psi) |
| Air flow [l/min] | 170 |
| A way of arc ignition | HF |
| Lenght [m] | 6 |
| Connection | 1/8" |
| Post gas flow time | 90 sek. (zalecane) |

PRODUCT CATEGORIES: [PLASMA](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.