

## Air filter AT-1000



**Product code:**

50500

### Product description

Fine compressed air filter AT-1000. Designed to remove water, oil and dusts from compressed air. It provides clean, dry and degreased air which is necessary for industrial applications.

This filter should be installed as close as possible to air-powered device. It is recommended to use fine filter AT-1000 together with other teams preparation of compressed air (such as: separator, pressure regulator, pre-filter, air dryer). Filter has on both sides female connectors 1/4", widely used in pneumatics. Robust housing and replaceable filter cartridges.

Examples of use:

- Plasma cutting
- Spray painting
- Pneumatic tools

### Technical parameters

<b>Accuracy [<math>\mu\text{m}</math>]</b>	0,25
<b>Max. work pressure [bar]</b>	8,5
<b>Max. flow rate [l/min]</b>	1250
<b>Work temperature [<math>^{\circ}\text{C}</math>]</b>	od -10 do +60
<b>Dimensions [mm]</b>	Ø 132 x 200

PRODUCT CATEGORIES: [MACHINES](#), [ACCESSORIES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.