

Compressed air extension cords WB Ø10mm [length 10m]



Product code:

PR10-10-N26

Product description

Elastyczne przedłużacze SPARTUS® Pneumatics do sprężonego powietrza wykonane z przewodu PVC (PCW) z dodatkowym wzmocnieniem tekstylnym (stylon) i powłoką zapewniającą dodatkową ochronę przed przetarciem. Ciśnienie robocze 20 bar (2 MPa) w zakresie temperatur -40°C do +70°C. Ciśnienie rozrywające > 40 bar (4 MPa). Przedłużacze okute są oryginalnymi szybkozłączami Rectus type 26 (DN 7,2).

Technical parameters

Diameter [mm]	10
Operating preassure [bar]	20

PRODUCT CATEGORIES: [HOSES](#), [HOSES](#), [ACCESSORIES](#), [ACCESSORIES](#), [HOSES AND QUICK COUPLER](#), [PNEUMATICS](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.