

Compressed air extension cords WT Ø8mm [length 10m]

Product code:

PR08-10-T26



Product description

Elastyczne przedłużacze do sprężonego powietrza wykonane z przewodu PVC (PCW) z dodatkowym wzmocnieniem tekstylnym (stylon). Ciśnienie robocze 20 bar (2 MPa) w zakresie temperatur -40°C do +70°C. Ciśnienie rozrywające > 40 bar (4 MPa). Przedłużacze okute są oryginalnymi szybkozłączami Rectus type 26 (DN 7,2).

Technical parameters

Diameter [mm]	8
Operating preassure [bar]	20

PRODUCT CATEGORIES: [HOSES](#), [HOSES](#), [ACCESSORIES](#), [ACCESSORIES](#), [HOSES AND QUICK COUPLER](#), [PNEUMATICS](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.