

Contact tip M6x28mm E-Cu 1,2mm



Product code:

25-20-012

Technical parameters

Type	E-Cu
Wire diameter [mm]	1.2
Application	250, 240/241, 360, PMT / MMT 25®, KMG 17 / 20 / 25®, MT 18 / 25®, MMG 18 / 20 / 22®, FE 20 / 25®, WS 30W®, PMT / MMT 30W®, FE 27 / 32®, PMT / MMT 27 / 32®

PRODUCT CATEGORIES: [FE, 20 / 25](#), [17 / 20 / 25](#), [18 / 20 / 22](#), [18 / 25](#), [25](#), [30W](#), [CONSUMABLES](#), [360](#), [27 / 32](#), [KMG](#), [MMG](#), [240 / 241](#), [MT](#), [250](#), [PMT/MMT](#), [WS](#), [FIT KEMPPi®](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.