

Contact tip M8x35mm E-Cu 1.6mm

Product code: 35-20-016

Technical parameters

Type	E-Cu
Wire diameter [mm]	1.6
Application	FE 42®, PMT / MMT 52W® - typ2, PMT / MMT 42® - typ2, PMT/MMT 52W® - typ1, PMT / MMT 42® -typ1, MT 51W®, FE 35®, PMT/ MMT / WS 42W® - typ2, PMT / MMT / WS 35® - typ2, PMT / MMT / WS 42W® - typ1, PMT / MMT / WS 35® - typ1, KMG 40®, MT 38®, MMT 40®, PMT 30 / 40 /50®, WS 30W®, PMT / MMT 30W®, FE 27 / 32®, PMT / MMT 27 /32®

PRODUCT CATEGORIES: [FE](#), [30W](#), [CONSUMABLES](#), [27 / 32](#), [KMG](#), [40](#), [38](#), [35](#), [51W](#), [30 / 40 / 50](#), [42](#), [MT](#), [PMT/MMT](#), [42 - TYPE1](#), [WS](#), [FIT KEMPPI®](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.