

Contact tip M8x35mm E-Cu for Al 0.8mm

Product code:

35-21-008

Technical parameters

Type E-Cu to Al

Wire diameter [mm] 0.8

Application FE 42®, FE 27 / 32®, FE 35®, KMG 40®, MT 38®, MT 51W®, MMT 40®, PMT 30 / 40 / 50®, PMT / MMT 27 / 32®, PMT / MMT 30W®, PMT / MMT / WS 35® - typ1, PMT / MMT / WS 35® - typ2, PMT / MMT 42® -typ1, PMT / MMT 42® - typ2, PMT / MMT / WS 42W® - typ1, PMT / MMT / WS 42W® - typ2, PMT/MMT 52W® - typ1, PMT / MMT 52W® - typ2, WS 30W®

PRODUCT CATEGORIES: [FE](#), [30W](#), [CONSUMABLES](#), [27 / 32](#), [KMG](#), [40](#), [38](#), [35](#), [51W](#), [30 / 40 / 50](#), [42](#), [MT](#), [PMT/MMT](#), [42 - TYPE1](#), [WS](#), [FIT KEMPPI®](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.