

## EasyTIG torch 26 / 4m / velve / X / SK35 connection

**Product code:** SPE26V-4-H200R-X-SK35

### Technical parameters

<b>Rating</b>	200A DC 150A AC
<b>Electrode diameter [mm]</b>	0.5, 1.0, 1.6, 2.0, 2.4, 3.2, 4.0
<b>Gas flow rate [L/min]</b>	7 - 20
<b>Duty cycle [%]</b>	35
<b>Series</b>	Easy
<b>Cooling</b>	gas
<b>Torch body</b>	26 [large parts]
<b>Torch body</b>	with valve
<b>Lenght [m]</b>	4
<b>Handle</b>	ribbed
<b>Package</b>	textile-rubber + 1m leather cable cover after grip
<b>Connections</b>	SK35

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.