

EasyTIG torch 26 / 8m / valve / X / SK35 connection

Product code: SPE26V-8-H200R-X-SK35

Technical parameters

Rating	200A DC 150A AC
Electrode diameter [mm]	0.5, 1.0, 1.6, 2.0, 2.4, 3.2, 4.0
Gas flow rate [L/min]	7 - 20
Duty cycle [%]	35
Series	Easy
Cooling	gas
Torch body	26 [large parts]
Torch body	with valve
Lenght [m]	4
Handle	ribbed
Package	textile-rubber + 1m leather cable cover after grip
Connections	SK35

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.