

EL120H Hand torch 12m HF (connection 9/16")



09010HF



Technical parameters

Standard	UNITORCH™
type of torch	hand
Type UniTorch™	EL120
Cutting current [A]	20 - 120
Gas	Air / N2
Duty cycle [%]	60
Operating pressure [bar]	4.8 - 5.2
Air flow [I/min]	200
A way of arc ignition	HF
Pilot arc [A]	20
Lenght [m]	12
Connection	9/16"

PRODUCT CATEGORIES: PLASMA TORCHES, PLASMA

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

 $\label{thm:constitute} \textit{The products do not constitute an offer within the meaning of the \textit{Civil Code}.}$