

EL120H-HY Hand torch 7.5m (connection POWERMAX1650®)



Product code: 09304

Technical parameters

|                          |               |
|--------------------------|---------------|
| Standard                 | UNITORCH™     |
| type of torch            | hand          |
| Type UniTorch™           | EL120-HY      |
| Cutting current [A]      | 20 - 120      |
| Gas                      | Air / N2      |
| Duty cycle [%]           | 60            |
| Operating pressure [bar] | 4.8 - 5.2     |
| Air flow [l/min]         | 200           |
| A way of arc ignition    | without HF    |
| Pilot arc [A]            | 20            |
| Lenght [m]               | 7.5           |
| Connection               | PowerMax1650® |

PRODUCT CATEGORIES: [PLASMA TORCHES](#), [PLASMA](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.