

EL120M Machine torch 6m HF (connection 9/16")

	Product code:	09020HF
Technical parameters		
Standard		UNITORCH™
type of torch		machine
Type UniTorch™		EL120
Cutting surrout [A]		20 120

Cutting current [A]	20 - 120
Gas	Air / N2
Duty cycle [%]	60
Operating pressure [bar]	4.8 - 5.2
Air flow [l/min]	200
A way of arc ignition	HF
Pilot arc [A]	20
Lenght [m]	6
Connection	9/16"

PRODUCT CATEGORIES: PLASMA TORCHES, PLASMA

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.