

FERROS 3D 1500 x 1000 x 200 [4 table legs with wheels L=450]

Product code:


SP28C-15-10-450M



* the price does not include shipping costs

Product description

USE THE SPACE FOR MORE EFFECTIVE WORK OFFERED BY FERROS TABLES!



EN-GJL-300 CAST IRON The casting of the top is made of EN-GJL-300 high strength cast iron characterized by high wear resistance. 25mm TABLE TOP The table top with a thickness of 25 mm guarantees the durability of the table and resistance to mechanical damage. MILLIMETRIC SCALE The applied millimeter scale facilitates precise assembly of the element to be processed. 3D SIDE It allows to expand the working surface and joining the table tops. D28 SYSTEM Drilled and chamfered holes 28mm.

Technical parameters

| Size of the work surface | 1500 x 1000 x 200mm |
|---------------------------------|--|
| Made | casted |
| Material | EN-GJL-300 cast iron acc. to EN 1561 |
| Table top thickness [mm] | 25 |
| Table horizontal precision [mm] | 0.1/1000 |
| Table vertical precision [mm] | 0.1/200 |
| Standard | D28 (drilled and milled holes 28mm diameter) |
| Carrying capacity | 2000kg/leg |
| Type of leg | with wheels |
| Leg length | 450mm |



| Number of legs#welding tables## | 4pcs |
|---------------------------------|-------|
| Overall table height [mm] | 760mm |
| Top weight [kg] | 535kg |

PRODUCT CATEGORIES: <u>WELDING TABLES</u>

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.