

Helmet SPARTUS Easy 130XT with true color filter - with hard hat and adapter



Product code:

080-10-130XTK

Product description

The SPARTUS® Easy 130XT automatic welding helmet with hard hat is designed to protect the welder's eyes and face from harmful radiation and welding spatters. It is perfect for MIG / MAG, TIG and MMA welding. It also has a grinding option. The automatic, high efficient filter protects the welder's eyes against harmful UV&IR radiation. After the arc ignition, this filter will switch from its natural light state to the darkened shade. After welding stops, it backs to normal immediately, according to the delay time set before. Fast lens reaction time - 1/25 000s is guaranteed thanks to the use of 4 very sensitive sensors.

The external control makes it easy to set the filter parameters during operation without removing the helmet. Thanks to them we can control the level of darkness (DIN 9-13), sensitivity, delay time and switch the operating mode to grinding. The Easy 130XT welding helmet is made of a durable and lightweight material. The multi-stage adjustment of the headgear allows to set the distance from filter to the welder's eyes, significantly increases the comfort of work and reduces the fatigue. The preview of the view is presented in real colors (true color).

Health and safety regulations require in many situations using of a protective helmet to cover the operator's head from injuries. The situations include for example: the works on bridges, on steel constructions, in large tanks as well as renovation and assembly works with boilers and their installations. Welding protection helmet SPARTUS® Easy 130XT is connected via a special adapter with hard hat. It provides increased protection of the welder from dangerous potential consequences of head injuries and ensures high comfort during long hours of use. Person, who uses protecting welding helmet with hard hat, meets stringent health and safety requirements in the workplace.

Technical parameters

| | |
|--|---|
| Brand | SPARTUS Easy |
| Application | MMA welding, TIG welding, MIG/MAG welding |
| Cartridge size [mm] | 110 x 90 x 9 |
| Active field of view [mm] | 98 x 55 |
| Filter optical class | 1 / 1 / 1 / 2 |
| Shading (standby) | DIN 4 |
| Variable welding shades (operating) | DIN 9 - 13 |
| UV/IR protection degree | do DIN16 |
| Sensors | 4 |
| Light to dark switching time | 1/25 000 s |
| Delay control of light to dark switching time | 0.25 - 0.8s |
| Powered | Solar cells |
| Grinding | YES |
| Adjustment knob and switch | external |
| Weight | 792g |

PRODUCT CATEGORIES: [SAFETY PRODUCTS](#), [WELDING HELMETS](#), [ACCESSORIES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.