

Hypercoolant

Product code:

50001

Product description

Product features:

- No health risks (based on organic propylene glycol);
- Ignition temperature > 95 ° C;
- Stable under normal conditions;
- Special risks Unknown

Specifications:

- color pink
- electrically neutral
- frost-hardy
- suitable for welding machines and plasma cutters.

Liquid coolant HYPERCOOLANT is created on the basis of ecological propylene glycol with added suitable corrosion inhibitors. It is special coolant – mostly recommended for cooling welding and plasma torches.

Technical parameters

Capacity

5l

PRODUCT CATEGORIES: [ACCESSORIES](#), [CHEMICAL](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.