

MAXIMUS 3D mobile lift welding table 2000 x 1000 (electrohydraulic version)

Product code:

SP28N-20-10-PE



*** the price does not include shipping costs**

Product description

GUARANTEE YOURSELF CONSTANT SUPPORT WITH MAXIMUS TABLES!



S355J2+N NITREDED STEEL

S355J2+N steel grade used to make the welding table gives high strength, impact and scratch resistance, whereas plasma nitrided welded top significantly enhances protection against corrosion and weld spatter.

25mm TABLE TOP

The table top with a thickness of 25 mm guarantees the durability of the table and resistance to mechanical damage.

MILLIMETRIC SCALE

The applied millimeter scale facilitates precise assembly of the element to be processed.

D28 SYSTEM

Drilled and chamfered holes 28mm.

The use of SPARTUS® mobile lift welding tables brings many benefits that translate into more effective and comfortable work.



HEIGHT PRECISE ADJUSTMENT

Setting the table top at the right customised height enhances the level of comfort during the performance of lengthy tasks, which has a significant impact on the work efficiency and welding quality. The working height of the lift (without the table top) is adjustable in the range from 530mm to 1000mm.



LIFT CAPACITY

Lifting system with a high capacity of maximum 2200kg (without the table top) allows you to load the unit with large-size elements and apply accessories to facilitate element assembly.

MOBILITY

High loads and tough working conditions on shop floors require the application of appropriate equipment. The lift system uses wheels, including two with a braking system, supporting safe and trouble-free movement of the welding table.

SAFETY

The mobile lift is equipped with two protections:

maintenance interlocking system



limit switch – crushing protection



The SPARTUS® mobile lift welding tables is a modern and convenient solution for professionals who value solid solutions that facilitate the work of welders.

Technical parameters

Size of the work surface	2000 x 1000 x 200mm
Made	welded with a protective coating (nitrided)
Material	S355J2+N steel acc. to EN 10025-2
Table top thickness [mm]	25
Table horizontal precision [mm]	0.1/1000
Table vertical precision [mm]	0.1/200
Standard	D28 (drilled and milled holes 28mm diameter)

Nominal capacity (table top + details) [kg]	2200
Overall table height [mm]	730 - 1200
lifting	electrohydraulic
Lifting speed [mm/s]	30
Lowering speed [mm/s]	40
Supporting structure	Table lift
Top weight [kg]	720
Jack weight [kg]	450
Input	~3× 400V ± 10% 50 / 60 Hz

PRODUCT CATEGORIES: [MAXIMUS](#), [WELDING TABLES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.