

MAXIMUS 3D mobile lift welding table 2400 x 1200 (electrohydraulic version)

Product code:

SP28N-24-12-PE



*** the price does not include shipping costs**

Product description

GUARANTEE YOURSELF CONSTANT SUPPORT WITH MAXIMUS TABLES!



S355J2+N NITREDED STEEL

S355J2+N steel grade used to make the welding table gives high strength, impact and scratch resistance, whereas plasma nitrided welded top significantly enhances protection against corrosion and weld spatter.

25mm TABLE TOP

The table top with a thickness of 25 mm guarantees the durability of the table and resistance to mechanical damage.

MILLIMETRIC SCALE

The applied millimeter scale facilitates precise assembly of the element to be processed.

D28 SYSTEM

Drilled and chamfered holes 28mm.

The use of SPARTUS® mobile lift welding tables brings many benefits that translate into more effective and comfortable work.



HEIGHT PRECISE ADJUSTMENT

Setting the table top at the right customised height enhances the level of comfort during the performance of lengthy tasks, which has a significant impact on the work efficiency and welding quality. The working height of the lift (without the table top) is adjustable in the range from 525mm to 1325mm.



LIFT CAPACITY

Lifting system with a high capacity of maximum 3000kg (without the table top) allows you to load the unit with large-size elements and apply accessories to facilitate element assembly.

SAFETY

The mobile lift is equipped with two protections:

maintenance interlocking system



limit switch - crushing protection



The SPARTUS® mobile lift welding tables is a modern and convenient solution for professionals who value solid solutions that facilitate the work of welders.

Technical parameters

Size of the work surface

2400 x 1200 x 200mm

Made

welded with a protective coating (nitrided)

Material

S355J2+N steel acc. to EN 10025-2

| | |
|--|--|
| Table top thickness [mm] | 25 |
| Table horizontal precision [mm] | 0.1/1000 |
| Table vertical precision [mm] | 0.1/200 |
| Standard | D28 (drilled and milled holes 28mm diameter) |
| Nominal capacity (table top + details) [kg] | 3000 |
| Overall table height [mm] | 730 - 1200 |
| lifting | electrohydraulic |
| Lifting speed [mm/s] | 30 |
| Lowering speed [mm/s] | 40 |
| Supporting structure | Table lift |
| Top weight [kg] | 960kg |
| Jack weight [kg] | 570kg |
| Input | ~3× 400V ± 10% 50 / 60 Hz |

PRODUCT CATEGORIES: [MAXIMUS](#), [WELDING TABLES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.