

Mobile weld fume extractor ClearStream Duo 2000 2m



Product code: SP030-06-302

Status: News

Order fulfillment time - 2 weeks

Product description

Mobile Welding Fume Extractors SPARTUS® ClearStream Duo 2000

ClearStream Duo 2000 is designed for effective filtering of dust generated by activities such as welding, grinding, cutting, and processing of plastics and metals. Utilizing two Vortex extraction arms, the device enables efficient removal of pollutants from two workstations. This model employs an advanced, three-stage filtration system. Preliminary cleaning is done using a metal filter that captures larger particles and sparks. Next, the main cartridge filter thoroughly removes finer contaminants, and final cleaning is provided by a fleece insert impregnated with activated carbon. ClearStream Duo 2000 is also equipped with an innovative system for automatic cleaning of the main filter using compressed air (it has its own 20-liter tank), which increases its efficiency and extends its lifespan. The device is recommended for applications requiring continuous air quality control.

Advanced filtration: Utilizes a three-stage filtration process, ensuring effective removal of various air contaminants.

High performance: Filtration capacity of 2000 m³/h ensures efficient air cleaning.

Full mobility: The housing equipped with wheels (including two swivel wheels) ensures easy movement.

Easy filter cartridge handling: The design provides easy access and handling of the filters, facilitating their regular cleaning and maintenance.



Applications:

Welding work requiring continuous extraction

Work at repair stations

Local ventilation (excluding corrosive and aggressively acting fumes or chemical gases)

Professional use

Protecting employees' health and improving working conditions

Standard equipment:

2 Vortex 160 extraction arms 2m

ClearStream 2000 mobile air ventilation system

Additional paid options:

LED lighting in the nozzle

Automatic operation sensor for welding processes

HEPA filter

EC motor

Made in EU

Technical parameters

Reach	2m
Flow	2000m ³ /h

Noise level	75dB(A)
Power	2,2kW
Input	~3x 400V ± 10% 50 / 60 Hz

PRODUCT CATEGORIES: [MACHINES](#), [MOBILE WELDING FUME EXTRACTORS](#), [FILTER VENTILATION SYSTEMS](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.