

NW1650H Machine plasma torch 7.5m (POWERMAX 1650 connection)



**Product code:**

NW03831CX-HY

**Technical parameters**

|                                 |   |
|---------------------------------|---|
| <b>Standard</b>                 | HYPERTHERM®                                       |
| <b>type of torch</b>            | machine   |
| <b>Type HYPERTHERM®</b>         | POWERMAX 1000 / 1250 / 1650 / 1100 T60 / 80 / 100 |
| <b>Cutting current [A]</b>      | 40-130  |
| <b>Gas</b>                      | Air / N2  |
| <b>Duty cycle [%]</b>           | 60  |
| <b>Operating pressure [bar]</b> | 4.6 - 5.5   |
| <b>Air flow [l/min]</b>         | 290   |
| <b>A way of arc ignition</b>    | without HF  |
| <b>Lenght [m]</b>               | 7.5   |
| <b>Connection</b>               | PowerMax1650®                                     |

PRODUCT CATEGORIES: [PLASMA TORCHES](#), [PLASMA](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.