

NW70H Hand plasma torch 6m (threaded connection)



Product code: NW03070N

In the order comments, please specify the type of nut (M16, M14, 3/8", 1/4", 1/8").

Technical parameters

Standard	CEBORA®
type of torch	hand
Type CEBORA®	P70 / P36 / P52®
Cutting current [A]	70
Gas	Air / N2
Duty cycle [%]	60
Operating pressure [bar]	4.5 - 5.0
Air flow [l/min]	150
A way of arc ignition	HF
Lenght [m]	6
Connection	M16, M14, 1/4", 1/8", 3/8"

PRODUCT CATEGORIES: [PLASMA TORCHES](#), [PLASMA](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.