

Screw compressor SP4A-315-200-10

Product code:

SP4A-315-200-10



Product description

The compressors of the SP3A and SP4A series are universal devices, with a simple design, for use in small plants, where the most important thing is low operating costs and reliable work. The use of low-power electric motors and low-speed screw modules resulted in increased durability of the moving parts.

Advantages of the device:

- low-noise operation (67-72 dB),
- belt drive enabling easy modification of performance and maximum pressure by changing the pulley ratios,
- simplified access to maintain the airend,
- microprocessor controller with idle run function,
- low weight,
- the possibility of installing the compressor on wheels or on shock absorbers,
- reliable screw airends by global manufacturers (GHH RAND) designed for continuous operation,
- asymmetric design rotor's profiles to generate maximum power and performance at minimum energy cost.

Technical parameters

Input	~3× 400V ± 10% 50 / 60 Hz
Max. Pressure [bar]	10
Capacity [l/min]	315
Power [kW]	3
Drive	direct
Noise level [dB(A)]	73
Connection [cal]	1/2
Weight [kg]	135
Dimensions [mm]	1550 x 570 x 1100
Tank capacity [L]	200

PRODUCT CATEGORIES: [MACHINES](#), [COMPRESSORS](#), [SCREW COMPRESSORS](#), [SCREW COMPRESSORS](#), [COMPRESSORS](#), [PNEUMATICS](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.