

Self-shielding flux cored wire, diameter 0.8 mm / 0.9 kg (D100) E71T-GS



Product code: SP900-100-08

Product description

Self-shielding flux cored wire for welding without gas shield (FCAW), creates a cover that protects the weld against oxygen, hermetically packed spool, used in agriculture, construction and production.

Technical parameters

Type	E71T-GS
Welding wire spool [kg]/[mm]	≤ 1 / 100
Wire diameter	0.8 [mm]

PRODUCT CATEGORIES: [MIG / MAG WELDING WIRES](#), [ELECTRODES AND WIRES](#), [ACCESSORIES](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.