

SP45H Hand plasma torch, 6m (central plug) 6 holes cover



Product code:

SP09635-SP2-6

Technical parameters

Standard	SPARTUS®
type of torch	hand
Type SPARTUS®	SP45
Cutting current [A]	40
Gas	Air / N2
Duty cycle [%]	60
Operating pressure [bar]	4.5 - 5
Air flow [l/min]	150
A way of arc ignition	without HF
Pilot arc [A]	18-22
Lenght [m]	6
Connection	central connector (6 holes)

PRODUCT CATEGORIES: [PLASMA TORCHES](#), [PLASMA](#)

NW ® is independent subject and not connected to ABITIG®, AMPHENOL®, ASPA®, BESTER®, BINZEL®, CEA®, CEBORA®, ESAB®, EWM®, FALTIG®, FRO®, FRONIUS®, HARRIS®, HYPERTHERM®, KJELLBERG®, L-TEC®, LINCOLN®, MAGNUM®, OTC®, SAF®, SHERMAN®, TELWIN®, THERMAL DYNAMICS®, TRAFIMET®, TUCHEL®.

Reference numbers and names belonged to above companies were called due to Property Right Law for buyer's convenience and they are related to code and spare part's description.

The products do not constitute an offer within the meaning of the Civil Code.